

SECURE AWARE HYBRID AODV PROTOCOL IN WIRELESS SENSOR NETWORK: A REVIEW

Dr Syed Umar

Professor, Department of Computer Science & Engineering, Malla Reddy (MR) deemed to be University, Hyderabad, syedumar@mrec.ac.in

Goli Madhuri

Assistant Professor, Department of computer science and engineering, Malla Reddy (MR) Deemed to be University, Hyderabad, golimadhurireddy120@gmail.com

Dikshendra Daulat Sarpate

Professor, Department of Artificial Intelligence & Data Science, ZEAL College of Engineering & Research, Pune, Email id -dikshendra@gmail.com

Gopala Soujanya

Assistant Professor, Department of computer science and engineering, Malla Reddy (MR) Deemed to be University, Hyderabad, Soujanyaachiluka52@gmail.com

B.Rani

Assistant Professor, Department of computer science and engineering, Malla Reddy (MR) Deemed to be University, Hyderabad, rani@mrec.ac.in

Abstract— Versatile Ad-Hoc Network is an independent arrangement of assortment of portable Hubs or nodes associated by remote associations. Hubs or nodes are freed to travel, every now and again change their position and sort out themselves into a system. Hubs or nodes contain remote transmitter and beneficiary that permit them to participate in remote system. Hubs or nodes in MANET having double conduct, they go about as switches just as registering gadgets. Constrained transmission capacity and changing geography results the issue of Congestion in MANETs.

Congestion and security issues are both solved in this work using bloom filter and congestion aware protocol hybrid combination in AODV protocol. The paper shows analysis of review of better energy, PDR, throughput and high speed of the wireless sensor network.

A remote sensor arrange (WSN) has significant applications, for example, remote ecological observing and target following. This has been empowered by the accessibility, especially as of late, of sensors that are littler, less expensive, and smart. These sensors are furnished with remote interfaces with which they can speak with each other to shape a system. The plan of a WSN relies essentially upon the application, and it must consider factors, for example, the earth, the application's structure targets, cost, equipment, and framework limitations.

Index Terms—Ad-Hoc Network, MANET, AODV protocol, Wireless Sensor Network

I. INTRODUCTION

The enormous uses of WSNs bring numerous difficulties regardless of whether these small sensor Hubs or nodes are battery controlled and sent haphazardly or deterministically in risky spots where customary framework-based system is for all intents and purposes infeasible. There are numerous run of the mill issues like constrained vitality assets, restricted figuring limit, open condition and remote availability makes the sensor arrange a disappointment more often than not. When sensor Hubs or nodes are sent, Hubs or nodes with a finite battery force ought to continue for quite a long time or years at a stretch with no intercession [1]. A significant structure issue in WSNs is to diminish the vitality utilization by the utilization of vitality moderating equipment, working framework and correspondence conventions. Further, among the correspondence conventions, the plan of directing plans is considerably progressively perplexing and should have the option to trade, process the data adequately and efficiently. It is important that transmission vitality that overwhelms by and large vitality utilization is relative to the separation between the transmitter and beneficiary. So as to structure a reasonable convention, it is essential to comprehend the boundaries that are pertinent to the applications. Not many of them are talked about here.

Self-Organizing Capability: Sensor Networks comprise of hundreds or thousands of sensor Hubs or nodes must make them compose capacity to speak with one another when they are sent in remote spots/hazardous spots without human observing framework.

Network Lifetime: It is constantly expected that the system ought to be useful as far as might be feasible. In this way, all parts of the hub, for example, equipment to the conventions must think about vitality efficiency [2].

Load adjusting: Routing conventions must adjust the heap among the entire sensor Hubs or nodes with the goal that organize lifetime can be improved.

Scalability: When the system develops in size, exorbitant correspondence overhead should not be presented regardless of whether it is unavoidable while building the way to the sink.

Latency: Data got from the sensor organize is time delicate. For example, a fire fighter may require opportune updates for knowing the present fire conditions though soil observing framework may require the report after at regular intervals.

Clustering: Grouping the sensor Hubs or nodes in to bunches fulfill the versatility objective and accomplish vitality efficiency with delayed system lifetime in enormous scope situations. Thus originators of steering conventions must think about the attributes of sensor Hubs or nodes, kinds of utilization and engineering prerequisites and so forth.

For these different calculations and conventions are been characterized out of which the most significant ones in the provisions of high vitality productivity is Low Energy Adaptive Clustering Hierarchy (LEACH) and its variations [3].

Systems have been rapidly making all through the latest couple of decades, varying from direct host-server structures to a thousand-center point WSN building. In equivalent, organizing threats have grown moreover. The further developed the system, the more broad the extent of potential network based attacks or dangers that could be performed to upset the dedicated functionalities of that organize. Replay network based attacks or dangers are among the most widely recognized and easily performed network based attacks or dangers. This line of investigation looks at the capability of Bloom diverts in tending to replay network based attacks or dangers performed on remote sensor systems and how they influence essentialness, throughput, and amounts of packages exchanged the system [4]. WSNs, AODV directing show, replay network based attacks or dangers, and Bloom channels are out and out ideas that make up the structure squares of this work, so they are discussed in detail in the going with subsections to give perusers an unrivaled perception of the general contemplations and approaches. WSNs are the eventual outcome of headways in the advancement fields of littler scope electro-mechanical structures (MEMS) and other related regions of investigation, for instance, correspondence arranges and introduced systems. An insignificant exertion, less power requesting, space viable system structure is open for different uses and purposes. The field of WSNs is a productive wellspring of utilizations in industry, military, prosperity practices, coherent investigation, and various fragments. Made out of practical sensors enacted by the general condition, WSNs can accumulate significant data, which would then have the option to be poor down for course of action purposes [5].

Data assembled by sensor systems are on a very basic level what the sensor center points perceive. Sensor center points, as spoke to it can separate light, heat, tenacity, sound, weight, or some other quantifiable sort of data that can be implied limit regards as demonstrated by what sort of sensor organize application is being utilized. Mobilizers and power generators are not commonly utilized in sensor centers. As such, it is fundamental to have WSNs worked in an issue that ponders the as of late referenced parts in order to keep up a commendable level of execution. WSN center points can be passed on in self-assertive or fixed situations to fill the need of sending. Not at all like specially appointed systems, WSNs are for the most part the more thickly used, but then, they are inclined to disillusionments in higher frequencies than impromptu dispersions. Notwithstanding that, WSNs rely upon communicate correspondence. Centers step by step gather their coordinating tables and start transmitting data subject to the courses they find, however impromptu systems are logically established on feature point correspondence. As for the size of WSNs, such a system comprises of center point numbers stretching out from tens to thousands in order to watch unequivocal consistent on the spot adjustments that may be shorewards, underneath the ground, or in wet situations, for instance, lowered or in soggy common environmental factors [6].

In LEACH and brought together (LEACH-C), two notable bunching based steering conventions which is talked about quickly in this segment, gives a lot more chances/challenges for growing new conventions. Filter receives 1) Randomized probabilistic model 2) Local data for information move 3) Low vitality media get to control 4) Application specific information preparing, for example, collection or pressure and so forth. However, by and by, it isn't fitting to consider just the probabilistic model or one boundary like vitality to choose the group heads (CH). More boundaries like separation to BS, focus and centrality can be incorporated to choose the CH. On the off chance that more boundaries are to be thought of, it is required to alter the convention with extraordinary delicate registering expertise based streamlining procedures.

As found in figure 1, an average remote sensor organize situation model, it comprises of Hubs or nodes, a base station where all sensor information is gotten from all the Hubs or nodes. All the Hubs or nodes in the wake of gathering information from explicit sensors send information to CH. These group heads send information to base station or to other CH relying upon whether the correspondence is a solitary bounce or a multi jump based individually.




Figure 1: General system model for cluster based WSN [7]

The overhauls in remote correspondence innovation empowered gigantic scope remote sensor systems (WSNs) arrangement. As a result of the capacity of simplicity of arrangement of sensor Hubs or nodes, remote sensor systems (WSNs) have a top notch scope of projects which joins observing of general condition and salvage missions. Typically remote sensor organize comprises of huge broad not many kinds of sensor Hubs or nodes. The all occasion is detected through the low vitality sensor hub which sent in arrange and the detected data is seeded to a base station. To convey essential information from the environmental factors in genuine time it is unimaginable with wired sensor systems while remote sensor systems are utilized for records arrangement and preparing in real time from condition. The encompassing circumstances inside the environmental factors are estimated through sensors and afterward estimations are handled with a reason to decide the circumstance precisely in area over the sensors [8]. Over a huge topographical territory enormous quantities of sensor Hubs or nodes are conveyed for precise observing. Due to the compelled radio scope of the sensor Hubs or nodes the upgrade in arrange size will build inclusion of territory anyway data (information) transmission for example Correspondence to the base station (BS) is made suitable with the help of middle Hubs or nodes.

The utilization of different remote gadgets like cell phones, GPS gadgets, PCs, RFID and distinctive electronic devices have become extra unavoidable, less expensive and fundamental in the present ways of life. The interest for correspondence and systems administration among those different remote gadgets has been quickened for one-of-a-type programs. Remote sensor systems starting here of view are the most recent pattern.

Impromptu Network (MANET) that is associated by remote connections is a self-arranging system of versatile Hubs or nodes. The gadgets uninhibitedly move toward any path and connections among these gadgets are changed oftentimes [9]. An agreeable system composed by assortment of sensor Hubs or nodes is a remote sensor arrange. Both of these systems fall into the class of foundation less remote systems as they do have any necessity with respect to framework during the arrangement.

II. PROBLEM FORMULATION OF WSN PROTOCOL

Remote sensor systems (WSNs) are viewed as one of the most noteworthy advances of the 21st century. In like manner, WSNs have been used in different applications in industry, prosperity observing, ecological checking, and other related fields. Regardless, the unprotected thought of WSN shows, for instance, the Ad-hoc On-Demand Distance Vector (AODV) Protocol makes them inclined to malevolent network based attacks or dangers. One such ambush is the replay attack. A lone sensor center point has compelled calculation and correspondence limits, anyway getting ready coordinating data through data structures with good reality multifaceted nature can prompt ensure about data securing and recognizing. Sensor center points have obliged essentialness resources, so this ambush can truly influence organize usefulness. In this work, Bloom channels are used to recognize the credibility of a package. Sensor center points will have the alternative to perceive credible and replayed packs along a way, in like manner improving a center point's choice with respect to whether it should transmit or discard the got bundle. The principle reason propels to deal with this territory is the significance of WSN which incorporates it empowers to give all basic data from sensor to base station and advances a quicker reaction if necessary. Here in this segment, the difficulties, issues or issues related with WSN is examined and as per that a work commitment in this field is have to make. Sensor arrange conventions and calculations have to possess self-sorting out capacities. each and every other exact component of sensor organize is the helpful endeavor of sensor Hubs or nodes. Sensor Hubs or nodes are reasonable with a locally available processor. In inclination to sending the uncooked data to the Hubs or nodes liable for the combination, they utilize their preparing aptitudes to territorially complete simple calculations and transmit best the ideal and in part handled data. Wi-Fi based Wireless sensor network utilizes a colossal style of utility and to affect those bundles in genuine worldwide conditions, researchers need more noteworthy green conventions and calculations. Planning a pristine convention or set of rules adapt to a couple of difficulties which can be need to be basically comprehended [10]. these difficulties are summed up underneath:

Physical Resource Constraints: The most extreme cutoff forced on the sensor organize is the insignificant sensor hub battery power. A sensor hub's amazing life is resolved legitimately by the vitality gracefully. The life expectancy of a system sensor is thusly determined through the force flexibly. Thusly, the fundamental issue with the design of a convention is vitality utilization. Limited machine electrical force and term of memory are on the whole different requirements which influence the measure of information that can be put away in singular sensor Hubs or nodes [11]. The technique should along these lines be clear and smooth. Discussion slack in the system sensor might be enormous in light of the fact that all Hubs or nodes in every single other type of correspondence share a limited way.

Ad-hoc Deployment: Network usage for WSNs depends on the application and impacts the steering convention's general execution. The organization can be unconstrained and deterministic. Specially appointed arrangement: hub sending in WSNs relies upon programming and effects on directing convention's general execution. The usage can be either unusual or deterministic.

On the off chance that the resulting appropriation of Hubs or nodes isn't generally uniform, highest quality level bunching transforms into important to permit availability and permit power green network activity. Between sensor verbal trade is ordinarily inside speedy transmission levels because of solidarity and data transfer capacity snags. consequently, it's miles most extreme perhaps that a course will envelop more than one remote jumps.

Fault Tolerance: a couple of sensor Hubs or nodes may moreover come up short or be blocked as a result of absence of solidarity, physical damage, or ecological obstruction. The disappointment of sensor Hubs or nodes should now not affect the general crucial the sensor organize. On the off chance that numerous Hubs or nodes come up short, MAC and directing conventions need to oblige development of most recent connections and courses to the realities assortment base stations. this can require effectively altering transmit powers and flagging statements on the common connects to lessen power utilization, or rerouting bundles through territories of the network where additional vitality is accessible [12]. in this way, two or three degrees of excess might be wished in a deficiency open minded sensor network.

Network Dynamics: limit of the network structures expect that sensor Hubs or nodes are fixed. be that as it may, versatility of both BS's or sensor Hubs or nodes is every so often indispensable in heaps of

bundles. Directing messages from or to moving Hubs or nodes is extra testing since way balance turns into a basic issue, further to quality, data transfer capacity and numerous others. besides, the detected marvel might be either powerful or static depending at the application, e.g., it's far unique in an objective recognition/observing programming, simultaneously as it is static in backwoods checking for early fire counteraction. checking static occasions allows the network to compositions in a responsive mode, really creating traffic when detailing. Dynamic exercises in most extreme applications require occasional detailing and subsequently produce sizable guests to be steered to the BS.

Multihop correspondence: The discussion form that remote sensor network utilizes are either single bounce or multi jump. since power utilization in Wi-Fi based Wireless frameworks is on the double corresponding to the rectangular of the space, single jump correspondence is extravagant in expressions of solidarity admission. Limit of the directing calculations utilizes multi jump correspondence variant considering it's undeniably more vitality proficient as far as quality admission in any case, with multi bounce discussion the Hubs or nodes which are nearer to the group head are underneath substantial site guests and might make holes close to the bunch head while their vitality ends.

Cluster Dynamics: Cluster elements way how the unprecedented boundaries of the group are resolved for example, the assortment of bunches in a particular system. In a couple of examples the assortment is presumably preassigned and in a couple of occasions it is dynamic. The group head plays the attribute of pressure notwithstanding transmission of realities. the hole between the bunch heads is a prime issue. it might be dynamic or might be set as per some base worth. If there should arise an occurrence of dynamic, there's a chance of shaping lopsided bunches. while confining it by some pre-relegated, insignificant separation might be amazing at times however this is an open exploration issue.

In a few applications, measurements must be brought inside a definite timeframe from the second it is detected, in some other case the information might be futile. in this manner, limited inertness for data dispatching is each other situation for time-bound bundles. in any case, in heaps of projects, protection of vitality, that is without a moment's delay identified with network lifetime, is mullied over unmistakably more basic than the five star of measurements sent. as the quality gets drained, the system can be required to diminish the extraordinary of the results a decent method to reduce the quality dissemination inside the Hubs or nodes and along these lines draw out the full network lifetime. thus, vitality cognizant steering conventions are required to hold onto this prerequisite [13].

Unattended Operation: in heaps of programming sensor systems is sent when, and after sending have no human intercession. subsequently, the Hubs or nodes themselves are responsible for reconfiguration if there should arise an occurrence of any alterations.

Attribute based Addressing: in view of the sheer amount of Hubs or nodes it isn't generally practical to allot IDs to Hubs or nodes in WSNs. records is gotten to from Hubs or nodes through traits no longer by method of IDs. This makes interruption into the framework more straightforward and implementing an assurance system extreme.

Safety: insurance is basic boundary in sensor systems. There must be a successful harmony between the little sensor organize parcels data transfer capacity particulars and security requests for simple correspondence in sensor systems (generally squeezing sources), which is the reason, contrasted with conventional systems, channel quality with proficient transmission is to be amplified.

III. CLUSTERING ALGORITHM IN WIRELESS SENSOR NETWORK

A WSN or Wireless sensor system is a game plan of Hubs or nodes in a particular locale where Hubs or nodes comprises of sensor, power gracefully and correspondence convention. WSN have a wide extent of usages in various fields. The grouping calculations are generally acclaimed for research-situated work. One of the most recent creating applications are in the Security, which permits between relationship of different articles or devices through the dubious conditions like separation, vitality, and so forth. Nevertheless, limited battery power is the huge concern of WSNs when appeared differently in relation to versatile gadgets on the system, which impacts the life expectancy of the system. From now on, a huge amount of investigates has been revolved around to restrain the vitality usage of the WSNs. Arranging of a dynamic grouping estimation is one of the different approaches as far as possible the vitality of the WSNs [14,15].

Advantages of Secure AODV in WSN:

There are several advantages of LEACH which are listed below:

- (1) The CH or cluster head gathers information from nodes and controls the traffic.
- (2) TDMA approach is used to manage any requests together.
- (3) Any node can become a cluster head to balance the energy amongst nodes.
- (4) energy efficient than other previous techniques.
- (5) High network lifetime and utilization of energy
- (6) very low packet loss

Secure AODV:

Systems have been quickly creating all through the most recent couple of decades, fluctuating from basic host-server structures to thousand-hub WSN engineering. In equal, organizing dangers have developed also. The more advanced the system, the more extensive the scope of potential network based attacks or dangers that could be performed to undermine the committed functionalities of that organize [16,17]. Since TESLA doesn't rely upon specific time synchronization, it has no interest for the profoundly exact time synchronization necessity that different conventions may not work appropriately without. Generally known for being used in databases, Bloom channels are randomized structures that test the participation of sections that channel through them. Recently have Bloom channels been used with expanding prevalence in PC organizing, despite the fact that the utilization of these consistent structures extends back to the 1970s when Burton Bloom presented them. Sprout channels were utilized for different applications, for example, word references, UNIX spell checkers, and putting away shaky passwords to forestall them. In spite of the fact that Bloom sifting may deliver bogus positives, its space productivity makes up for that accuracy inadequacy [18,19]. Blossom channels can rescue vitality stockpiles in various levels as per how large the WSN is and to what extent the way of transmission is.

Disadvantages of Existing System:

1. Security is less
2. Increasing the duplicates
3. Complexity more

Advantages of Existing System:

1. Its space efficiency compensates
2. Providing the security by using bloom filters

IV. CONCLUSION

The parameters can be further improved by the use of other special computing algorithms like ANN or ACO for further scope. Also, this can be efficiently used for high speed and high energy system network applications. Headway in the electronic and correspondence industry has essentially prompted the need of security and investigation in the framework. To accomplish this, fundamentally require sensor-based center point stations or Hubs or nodes for appropriate information move of the basic boundaries of the earth. Sensor Networks are significant field of examination nowadays as it is imperative to move sensors basic information to various area. Accordingly, it is imperative to improve the proficiency of the framework by improving the speed of the system and upgrading its capacity to move the basic information proficiently.

References

- [1] N. AlMansour and S. Alahmadi, "Secure Ad Hoc On-Demand Distance Vector Routing Protocol in WSN," 2018.
- [2] S. Alkhuder, "Securing Ad-Hoc On-Demand Distance Vector Protocol in Wireless Sensor Networks: Working with What the Node Can Offer 2018.
- [3] Naveen Sai Bommina, Nandipati Sai Akash, Uppu Lokesh, Dr. Hussain Syed, Dr. Syed Umar, "A Hybrid Optimization Framework for Enhancing IoT Security via AI-based Anomaly Detection",

International Journal on Recent and Innovation Trends in Computing and Communication, (2023)
ISSN: 2321-8169 Volume: 11 Issue: 3.

- [4] P. Papadimitratos and Z. J. Haas, "Secure on-demand distance vector routing in ad hoc networks," 2005.
- [5] Ye Tung, M. Alkhatib and Q. S. Rahman, "Security Issues in Ad-Hoc on Demand Distance Vector Routing (AODV) in Mobile Ad-Hoc Networks," 2006.
- [6] R. S. Mangrulkar and M. Atique, "Trust based secured adhocOn demand Distance Vector Routing protocol for mobile adhoc network," 2010 Sixth International conference on Wireless Communication and Sensor Networks, Allahabad, 2010.
- [7] Uppu Lokesh, Naveen Sai Bommina, Nandipati Sai Akash, Dr. Hussain Syed, Dr. Syed Umar, "Designing Energy-Efficient and Secure IoT Architectures Using Evolutionary Optimization Algorithms", International Journal of Applied Engineering & Technology, Vol. 4 No.2, September, 2022.
- [8] J. T. Kim, J. Kho, C. Lee, D. Lee, C. Bang and G. Lee, "A Safe AODV (Ad Hoc On-Demand Distance Vector) Security Routing Protocol," 2008.
- [9] I. F. Akyildiz, W. Su, Y. Sankarasubramaniam, and E. Cayirci, "Wireless sensor networks: a survey. Computer Networks" 2002.
- [10] A. Broder, and M. Mitzenmacher, "Network Applications of Bloom Filters: A Survey". In Internet Mathematics 2010.
- [11] Habeeb, M. S., & Babu, T. R. (2022). Network intrusion detection system: a survey on artificial intelligence-based techniques. *Expert Systems*, 39(9), e13066.
- [12] Habeeb, M. S., & Babu, T. R. (2024). Coarse and fine feature selection for network intrusion detection systems (IDS) in IoT networks. *Transactions on Emerging Telecommunications Technologies*, 35(4), e4961.
- [13] Habeeb, M. S. (2024). Predictive analytics and cybersecurity. *Intelligent Techniques for Predictive Data Analytics*, 151-169.
- [14] Naveen Sai Bommina , Nandipati Sai Akash, Uppu Lokesh , Dr. Hussain Syed , Dr. Syed Umar, "Privacy-Preserving Federated Learning for IoT Devices with Secure Model Optimization", *International Journal of Communication Networks and Information Security (IJCNIS)*, (2021), 13(2), 396–405.
- [15] Habeeb, M. S., & Babu, T. R. (2024, October). Enhancing IoT Security Through Advanced Feature Selection and Deep Learning. In *International Conference on Computing and Communication Networks* (pp. 37-49). Singapore: Springer Nature Singapore.
- [16] Nandipati Sai Akash, Naveen Sai Bommina, Uppu Lokesh, Hussain Syed, Syed Umar, "Optimized Block Chain-Enabled Security Mechanism for IoT Using Ant Colony Optimization", *International Journal on Recent and Innovation Trends in Computing and Communication*, (2023), 11(10), 1226–1233.
- [17] Thakre N, Nimma D, Turukmane AV, Singh AK, Rohatgi D, Bangaru B (2024) Dynamic path planning for autonomous robots in forest fire scenarios using hybrid deep reinforcement learning and particle swarm optimization. *Int J Adv Comput Sci Appl* 15(9).
- [18] Umar, Syed, Bommina Naveen Sai, Nagineni Sai Lasya, Doppalapudi Asutosh, and LohithaRani. "Machine Learning based Sentiment Analysis of Product Reviews Using DeepEmbedding." *Journal of Optoelectronics Laser* 41, no. 6(2022): 108-113.
- [19] M. Mukhedkar, D. Rohatgi, V.A. Vuyyuru, K.V.S.S. Ramakrishna, Y.A. Baker El-Ebiary, V.A. Asir Daniel, "Feline wolf net: A hybrid lion-grey wolf optimization deep learning model for ovarian cancer detection", *Int. J. Adv. Comput. Sci. Appl.*, 14 (9) (2023)